

MOSER, PATTERSON & SHERIDAN, L.L.P.

Attorneys at Law
3040 Post Oak Boulevard, Suite 1500
Houston, Texas 77056-6582
Telephone (713) 623-4844
Facsimile (713) 623-4846
www.mpsllp.com

FACSIMILE COVER SHEET

DATE: July 23, 2003	FILE NO: Serial Number: 09/931,324 AMAT/4184/ETCH/CHMBR/JB1
TO: Examiner Binh X. Tran	FAX NO: 703/872-9442
COMPANY: USPTO	
FROM: Ari Pramudji	PAGE(S): 6 with cover
MESSAGE:	Original to Follow <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

Proposed Amendments 07/23/03

C:\WRPORTBL\IMANA\CEVR\ENDERSON\213735_1.DOC

CONFIDENTIALITY NOTE

The document accompanying this facsimile transmission contains information from the law firm of Moser, Patterson & Sheridan, L.L.P. which is confidential or privileged. The information is intended to be for the use of the individual or entity named on this transmission sheet. If you are not the intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this faxed information is prohibited. If you have received this facsimile in error, please notify us by telephone immediately so that we can arrange for the retrieval of the original documents at no cost to you.

Received from <+7136234846> at 7/23/03 6:12:33 PM [Eastern Daylight Time]

PROPOSED AMENDMENTS 07/23/03

1. (Previously Presented) An apparatus for processing a substrate, comprising:
 - a chamber having a first electrode disposed therein;
 - a substrate support disposed in the chamber and providing a second electrode in the chamber;
 - a high frequency power source electrically connected to either the first or second electrode;
 - a low frequency power source electrically connected to either the first or second electrode; and
 - one or more variable impedance elements connected to the first and/or second electrode, wherein each variable impedance element is disposed between the first and/or second electrode and an electrical ground.
2. (Original) The apparatus of claim 1, wherein the first electrode comprises a gas distributor.
3. (Original) The apparatus of claim 1, wherein the first electrode and the second electrode form parallel plate electrodes.
4. (Original) The apparatus of claim 1, wherein the chamber is configured as an etch chamber.
5. (Original) The apparatus of claim 1, wherein the high frequency power source is adapted to deliver power between about 13.56 MHz and about 500 MHz.
6. (Original) The apparatus of claim 1, wherein the low frequency power source is adapted to deliver power between about 100 kHz and about 20 MHz.

7. (Original) The apparatus of claim 1, wherein the variable impedance elements comprise at least one inductor and at least one capacitor.
8. (Original) The apparatus of claim 1, wherein the variable impedance elements comprise at least one inductor and at least one variable capacitor.
9. (Previously Presented) An apparatus for processing a substrate, comprising:
 - a chamber having a first electrode disposed therein;
 - a substrate support disposed in the chamber and providing a second electrode in the chamber;
 - a high frequency power source electrically connected to either the first or second electrode;
 - a low frequency power source electrically connected to either the first or second electrode; and
 - one or more variable impedance elements connected to the first and/or second electrode, wherein each variable impedance element is disposed between the first and/or second electrode and an electrical ground, wherein the variable impedance elements are adapted to tune a self bias voltage division between the first and second electrodes.
10. (Original) The apparatus of claim 1, wherein the variable impedance elements are adapted to tune at least one resonant impedance at a frequency selected from at least one of the low frequency and the high frequency.
11. (Original) The apparatus of claim 1, wherein the variable impedance elements are adapted to tune a first resonant impedance at the low frequency and a second resonant impedance at the high frequency.
12. (Currently Amended) The apparatus of claim ~~44~~ 1, wherein the high frequency power and the low frequency power are delivered to one electrode and

at least one of the variable impedance elements is connected to the other electrode.

13. (Previously Presented) The apparatus of claim 11, wherein the high and low frequency power are delivered to opposite electrodes, wherein each electrode is connected to one of the variable impedance elements.

14. (Original) An apparatus for delivering power to a process chamber having a first electrode and a substrate support forming a second electrode, comprising:

a high frequency power source electrically connected to the first electrode;

a low frequency power source electrically connected to the first electrode;

and

a variable impedance element connected between the substrate support and an electrical ground.

15. (Original) The apparatus of claim 14, wherein the high frequency power source is adapted to deliver power between about 13.56 MHz and about 500 MHz.

16. (Original) The apparatus of claim 14, wherein the low frequency power source is adapted to deliver power between about 100 kHz and about 4 MHz.

17. (Original) The apparatus of claim 14, wherein the variable impedance element comprises at least one inductor and at least one capacitor.

18. (Original) The apparatus of claim 14, wherein the variable impedance element comprises at least one inductor and at least one variable capacitor.

19. (Previously Presented) An apparatus for delivering power to a process chamber having a first electrode and a substrate support forming a second electrode, comprising:
a high frequency power source electrically connected to the first electrode;
a low frequency power source electrically connected to the first electrode;
and
a variable impedance element connected between the substrate support and an electrical ground, wherein the variable impedance element is adapted to tune a self bias voltage division between the first electrode and the substrate support.
20. (Original) The apparatus of claim 14, wherein the variable impedance element is adapted to tune at least one resonant impedance at a frequency selected from at least one of the low frequency and the high frequency.
21. (Original) The apparatus of claim 14, wherein the variable impedance element is adapted to tune a first resonant impedance at the low frequency and a second resonant impedance at the high frequency.
22. (Original) The apparatus of claim 14, wherein the first electrode comprises a gas distributor.
23. (Original) The apparatus of claim 14, wherein the first electrode and the substrate support are disposed to form parallel plate electrodes.
24. (Original) The apparatus of claim 14, wherein the chamber is configured as an etch chamber.
25. (New) The apparatus of claim 1, wherein the variable impedance elements are configured to enhance ion acceleration toward the second electrode.

26. (New) The apparatus of claim 1, wherein the variable impedance elements are configured to adjust radio frequency power delivered to a processing region disposed between the first and second electrode.

27. (New) The apparatus of claim 1, wherein the variable impedance elements are configured to vary a voltage drop across a processing region disposed between the first and second electrode.

213566v1